

RGBW


Lighting Control with DMX





DMX Overview

Remote DMX Decoder




500mA or 700mA CC from DMX decoder

DMX Cable

Power 24 VDC for decoder

Integrated CV DMX Decoder




Power 220 VAC

Power 230 VAC for LED driver

Power 12 VDC for DMX controller

ID DMX




Power 220 - 240 VAC

Small scale DMX System

Up to 32 RGBW luminaires / Up to 300m distance

Applicable for RGBW luminaire with **Remote DMX Decoder**



Accessories



DMX Controller Nicolaudio STICK-KE2
AUN-DMX-0023-00



DMX Controller Nicolaudio SLESA-U9
AUN-DMX-0024-00



DMX Controller Nicolaudio SLESA-U10
AUN-DMX-0025-00



Splitter DMX in IP67 Aluminium Box.
AUN-DMX-0027-01



LED Constant Voltage Driver 24VDC
72W.
AUN-DRG-0027-00



LED Constant Voltage Driver 24VDC
150W.
AUN-DRG-0011-00



LED Constant Voltage Driver 24VDC
200W.
AUN-DRG-0024-00



4CH DMX512/ RDM Decoder with
24Vdc Input and 4x500mA 4x16W
Output in IP67 GFR Polymer Box.
AUN-DRG-0113-01



IP67 Water Tight Connecting Device, 3
Pole, Cable Diameter 4.5 - 11mm. [DMX]
AUN-CON-0022-00



IP67 Water Tight Connecting Device with
Distribution block, 3 pole,
1 input, 2 outputs, Cable Diameter
4.5 - 11mm. [DMX]
AUN-CON-0023-00



IP68 Water Tight Connecting Device, 3
Pole, Cable Diameter 5.0 - 9.5mm.
AUN-CON-0009-00




IP68 Water Tight Connecting Device with
Distribution block, 3 pole,
1 input, 2 outputs, Cable Diameter
5.0 - 9.5mm.
AUN-CON-0010-00

Medium scale DMX System

Up to 256 RGBW luminaires / Up to 300m distance


Applicable for RGBW luminaire with **Remote DMX Decoder**



Small scale DMX System

Up to 32 RGBW luminaires / Up to 300m distance

Applicable for RGBW luminaire with **Integrated CV DMX Decoder**



Accessories



DMX Controller Nicolaudie STICK-KE2
AUN-DMX-0023-00



DMX Controller Nicolaudie SLESA-U9
AUN-DMX-0024-00



DMX Controller Nicolaudie SLESA-U10
AUN-DMX-0025-00



Splitter DMX in IP67 Aluminium Box.
AUN-DMX-0027-01



LED Constant Voltage Driver 24VDC
72W.
AUN-DRG-0027-00



LED Constant Voltage Driver 24VDC
150W.
AUN-DRG-0011-00



LED Constant Voltage Driver 24VDC
200W.
AUN-DRG-0024-00



IP67 Water Tight Connecting Device, 3
Pole, Cable Diameter 4.5 - 11mm. [DMX]
AUN-CON-0022-00



IP67 Water Tight Connecting Device with
Distribution block, 3 pole,
1 input, 2 outputs, Cable Diameter
4.5 - 11mm. [DMX]
AUN-CON-0023-00



IP68 Water Tight Connecting Device, 3
Pole, Cable Diameter 5.0 - 9.5mm.
AUN-CON-0009-00




IP68 Water Tight Connecting Device with
Distribution block, 3 pole,
1 input, 2 outputs, Cable Diameter
5.0 - 9.5mm.
AUN-CON-0010-00

Medium scale DMX System

Up to 256 RGBW luminaires / Up to 300m distance


Applicable for RGBW luminaire with **Integrated CV DMX Decoder**



Small scale DMX System

Up to 32 RGBW luminaires / Up to 300m distance

Applicable for RGBW luminaire with **ID DMX**



Accessories


- DMX Controller Nicolaudie STICK-KE2 AUN-DMX-0023-00
- DMX Controller Nicolaudie SLESA-U9 AUN-DMX-0024-00
- DMX Controller Nicolaudie SLESA-U10 AUN-DMX-0025-00
- Splitter DMX in IP67 Aluminium Box. AUN-DMX-0027-01

- IP67 Water Tight Connecting Device, 3 Pole, Cable Diameter 4.5 - 11mm. [DMX] AUN-CON-0022-00
- IP67 Water Tight Connecting Device with Distribution block, 3 pole, 1 input, 2 outputs, Cable Diameter 4.5 - 11mm. [DMX] AUN-CON-0023-00
- IP68 Water Tight Connecting Device, 3 Pole, Cable Diameter 5.0 - 9.5mm. AUN-CON-0009-00
- IP68 Water Tight Connecting Device with Distribution block, 3 pole, 1 input, 2 outputs, Cable Diameter 5.0 - 9.5mm. AUN-CON-0010-00

Medium scale DMX System

Up to 256 RGBW luminaires / Up to 300m distance

Applicable for RGBW luminaire with **ID DMX**





DMX
RGBW


Remote
DMX
Decoder



ARC (DMX)
Inground uplighter



ARC




Specification

- High-pressure Die Cast Aluminium alloy body and components.
- Front cover in 316 stainless steel brush finished.
- Recessed housing made of GFR polymer.
- Luminaire withstands a maximum static load of 1000 kg.
- Nano Ceramic surface conversion, resistant to corrosive environment. UniShield-16
- Impact resistant safety tempered glass cover. Able to withstand the temperature up to 250°C.
- Glass flushes to the front cover, no accumulation of dust and water.
- Molded PC lens from renowned manufacturers in various light distribution patterns.
- Post-cured treated silicone gasket.
- External screws are in stainless steel with protection grease.
- Cable entry protected by M20 cable gland.
- High efficiency LED module utilized chips from world renowned manufacturer.
- Driver is not included and has to be ordered separately.
- The water drainage system must be tested to ensure that it is working sufficiency and efficiency.



Luminaire Performance	610 – 680 lm 22 W 27 – 30 lm/W
Beam Options	<div>Narrow</div> <div>Medium</div> <div>Wide</div>
Color Temperature	RGBW
Controller	Remote DMX Decoder

Accessories

Honey comb louver	CV Driver	DMX Decoder
Splitter DMX	Cable	XLR 3 pin
IP67 Water Tight	IP68 Water Tight	STICK KE2
SLESA		



Mini QUARK [DMX]
Inground uplighter



Specification

- High-pressure Die Cast Aluminium alloy body and components.
- Front cover in 316 stainless steel brush finished.
- Recessed housing made of GFR polymer.
- Luminaire withstands a maximum static load of 1000 kg.
- Nano Ceramic surface conversion, resistant to corrosive environment. UniShield-16
- Impact resistant safety tempered glass cover. Able to withstand the temperature up to 250°C.
- Glass flushes to the front cover, no accumulation of dust and water.
- Molded PC lens from renowned manufacturers in various light distribution patterns.
- Post-cured treated silicone gasket.
- External screws are in stainless steel with protection grease.
- Cable entry protected by M20 cable gland.
- High efficiency LED module utilized chips from world renowned manufacturer.
- Driver is not included and has to be ordered separately.
- The water drainage system must be tested to ensure that it is working sufficiency and efficiency.

Luminaire Performance	1440 – 2070 lm 22 – 32 W 57 – 73 lm/W
Beam Options	<div> </div>
Color Temperature	RGBW
Controller	Remote DMX Decoder

Accessories		
Honey comb louver	Softening filter	CV Driver
DMX Decoder	Splitter DMX	Cable
IP67 Water Tight	IP68 Water Tight	XLR 3 pin
STICK KE2	SLESA	



Remote
DMX
Decoder





VAREE
Wall Recess



VAREE
Spotlight



VAREE



Specification

- Supreme corrosion proof Under Water grade Stainless Steel.
- Injected GFR Engineering Polymer body component.
- Wall recessed housing made of GFR polymer.
- Impact resistant safety tempered glass cover.
- Molded PC lens from renowned manufacturers in various light distribution patterns.
- Post-cured treated silicone gasket.
- Marine grade 316 stainless steel screw.
- Cable entry protected by M16 cable gland.
- High efficiency LED module utilized chips from world renowned manufacturer.
- Driver is not included and has to be ordered separately.
- Pre-wired with 5x1.0 sqmm. PP + TPE cable. VDE approved.
- Installation work has to be carried on according to the enclosed installation manual.
- To avoid over-heating, this luminaire has to use under water only.

Luminaire Performance	1250 – 1560 lm	24 W	52 – 65 lm/W
Beam Options			
Color Temperature	RGBW		
Controller	Remote DMX Decoder		

Accessories

	Honey comb louver		Softening filter		CV Driver
	DMX Decoder		Splitter DMX		Cable
	IP67 Water Tight		IP68 Water Tight		XLR 3 pin
	STICK KE2		SLESA		




DMX
RGBW

Integrated
CV DMX
Decoder



KUBIK Optic – Ground Mount [DMX]
Spotlight



Specification

- High-pressure Die Cast Aluminium alloy body and components.
- Nano Ceramic surface conversion, resistant to corrosive environment. UniShield-16
- Impact resistant safety tempered glass cover.
- Glass flushes to the front cover, no accumulation of dust and water.
- Molded PC lens from renowned manufacturers in various light distribution patterns.
- Adjustable aiming unit through graduated scale.
- Post-cured treated silicone gasket.
- External screws are in stainless steel with protection grease.
- Cable entry protected by M20 cable gland.
- High efficiency LED module utilized chips from world renowned manufacturer.
- Driver is not included and has to be ordered separately.
- Pre-wired cable from factory.
- Pre-wired with 2x1.0 sqmm. HO7RN-F neoprene cable. IMQ approved.
- Pre-wired with shielded DMX cable.
- Installation work has to be carried on according to the enclosed installation manual.
- Available with remote driver.

Available Color



Luminaire Performance	1420 – 1510 lm 24 W 59 – 62 lm/W			
Beam Options	Medium	Wide	Elliptical H	Elliptical V
Color Temperature	RGBW			
Controller	Integrated DMX Decoder			

Accessories

	Honey comb louver		Softening filter		CV Driver
	Glare Shield		Splitter		Tree strap
	Pole clamp		Cable		Splitter DMX
	IP67 Water Tight		IP68 Water Tight		XLR 3 pin
	STICK KE2		SLESA		




DMX
RGBW

ID
DMX



ALPHA

Medium ALPHA Round – Gear [DMX] Spotlight



Features

- Designed, Manufactured and tested according to IEC 60598.
- LM6 Die Cast Aluminium body.
- Stainless steel screws.
- Nano Ceramic surface conversion.
- Double layer coating.
- Safety glass cover.
- Post-cured silicone gasket.
- High quality LED module.
- Weather proof TPE grommet.
- Installation must be carried out according to the enclosed product manual.
- High CC quality DMX driver
- Equipped with 10kV surge protection device.
- Pre-wired with shielded DMX cable.

Available Color



















Luminaire Performance	1440 – 1630 lm 27 W 53 – 60 lm/W			
Beam Options	Medium	Wide	Elliptical H	Elliptical V
Color Temperature	RGBW			
Controller	ID and Integrated DMX Decoder			

Accessories

	Aluminium pole		Steel pole		Glare Shield Cap
	Honey comb louver		Softening filter		Earth spike
	Tree strap		Pole clamp		Mounting Arm

*Please see Poles & Anchor bolt section for pole mounting options

Ordering Code	Product Name		
LED Constant Voltage Driver			
	AUN-DRG-0027-00	LED Constant Voltage Driver 24Vdc 72W.	for ARC, KUBIK, QUARK, VAREE
	AUN-DRG-0011-00	LED Constant Voltage Driver 24Vdc 150W.	for ARC, KUBIK, QUARK, VAREE
	AUN-DRG-0024-00	LED Constant Voltage Driver 24Vdc 200W.	for ARC, KUBIK, QUARK, VAREE
	AUN-DRG-0113-01	4CH DMX512/ RDM Decoder with 24Vdc Input and 4x500mA 4x16W Output In IP67 GFR Polymer Box.	for ARC, KUBIK, QUARK, VAREE
DMX Controller			
	AUN-DMX-0023-00	DMX Controller Nicolaudio STICK-KE2	for ARC, KUBIK, QUARK, VAREE
	AUN-DMX-0024-00	DMX Controller Nicolaudio SLESA-U9	for ARC, KUBIK, QUARK, VAREE
	AUN-DMX-0025-00	DMX Controller Nicolaudio SLESA-U10	for ARC, KUBIK, QUARK, VAREE
	AUN-DMX-0026-00	XLR 3 Pin Male Connector with UNITRONIC Li2YCYv (TP) cable length 1000mm. [DMX]	for ARC, KUBIK, QUARK, VAREE
	AUN-DMX-0027-00	Splitter DMX in IP67 Aluminium Box.	for ARC, KUBIK, QUARK, VAREE
Connector and Distribution Box			
	AUN-CON-0022-00	IP67 Water Tight Connecting Device, 3 Pole, Cable Diameter 4.5 - 11mm. [DMX]	for ARC, KUBIK, QUARK, VAREE
	AUN-CON-0023-00	IP67 Water Tight Connecting Device with Distribution block, 3 pole, 1 input, 2 outputs, Cable Diameter 4.5 - 11mm. [DMX]	for ARC, KUBIK, QUARK, VAREE
	AUN-CON-0009-00	IP68 Water Tight Connecting Device, 3 Pole, Cable Diameter 5.0 - 9.5mm.	for ARC, KUBIK, QUARK, VAREE
	AUN-CON-0010-00	IP68 Water Tight Connecting Device with Distribution block, 3 pole, 1 input, 2 outputs, Cable Diameter 5.0 - 9.5mm.	for ARC, KUBIK, QUARK, VAREE
Cable			
	ATR-CAB-0006-00	Cable UNITRONIC Li2YCYv (TP) length 2000mm. [DMX]	for ARC, KUBIK, QUARK, VAREE
	AUN-CAB-0040-00	Cable HO7RN-F 2x1sqmm length 2000mm.	for ARC, KUBIK, QUARK, VAREE
	AUN-CAB-0039-00	Cable HO7RN-F 3x1sqmm length 2000mm.	for ARC, KUBIK, QUARK, VAREE

DMX control option RGBW

✦ Ideal Application



Unilamp Co., Ltd.

461 Ramintra Road, Kannayao, Bangkok 10230 Thailand

Tel : +66[0]2 943 2420-1, +66[0]2 946 4170-1

Fax : +66[0]2 943 2419

unilamp@unilamp.co.th | online@unilamp.co.th



www.unilamp.co.th